

**BATTERY STRAPPING TOOL FOR PLASTIC STRAP P.P.— P.E.T.
DIGITAL CONTROL — FLAT AND ROUND SURFACE**

TECHICAL DATA / APPLICATIONS :


Compact, easy to use and versatile battery strapping tool equipped by new **Li-ion Battery**. Reliable to be used in industrial medium / heavy duty applications. The tool is suitable for strap size 16mm (5/8") up to 19mm (3/4"). One battery is provided with the tool; the battery recharger is considered as an optional.

Package type	Flat surface (minimum lenght 120mm—5") Round surface (min. diam. 700mm—28")
Strap quality	PP / PET
Strap Width	From 16mm up to 19mm (5/8" - 3/4")
Strap thickness	From 0,8mm up to 1,3mm PET From 0,8mm up to 1,0mm PP
Max. Tension	3400 N
Max. Tension speed	Around 13 mt/min
Joint type	Friction weld seal
Weight	Around 4,0 Kg (battery included)
Order code Digit Power	126.990.810

- * Li-ion BATTERY 14.4 V — 3.0 Ah
- * HIGH PERFORMANCES
- * NEW SEALING LEVER
- * LIGHT AND SMALL
- * ERGONOMIC HANDLE



NEW DIGITAL ADJUSTMENT SYSTEM FOR TENSION AND SEALING TIME



FAST CHARGER FOR NEW LI-ION BATTERY

INSERT THE BATTERY CARTRIDGE INTO CHARGER UNTIL IT STOPS, ADJUSTING TO THE GUIDE OF CHARGER

TERMINAL COVER OF CHARGER CAN BE OPENED WITH INSERTING AND CLOSED WITH PULLING OUT THE BATTERY CARTRIDGE



WHEN THE BATTERY CARTRIDGE IS INSERTED THE RED CHARGING LIGHT WILL LIGHT UP AND CHARGING WILL BEGIN

WITH FINISH OF CHARGE, THE CHARGING LIGHT WILL CHANGE FROM RED ONE TO GREEN ONE



NEW Li-ion BATTERY 14.4 V—3.0 Ah

- * HIGHT CAPACITY
- * NO MEMORY EFFECT
- * LIGHT AND COMPACT
- * BUILT-IN MEMORY CHIP