



PACKAGING

888-922-1622

WWW.IPACK.COM

New generation of battery powered plastic strapping tools for mobile strapping applications

This new, most versatile plastic strapping tool is a further development of the famous and well established P320 and P321 models. The new tool is very user-friendly and suitable for most applications in all industrial sectors. Tensioning as well as sealing cycles are activated by pressing a lever with the thumb.



Characteristics

Strapping qualities:		Polypropylene (PP) and Polyester (PET)
Strapping dimensions:	widths	10.0 – 16.0 mm / 3/8 – 5/8"
	thicknesses	0.40 – 1.05 mm / .016 - .041"
Weight:		4.4 kg / 9.7 lbs
Dimension:		L335 x W159 x H126 mm
Average seal strength:		up to 80% (dependent on strap quality)
Strap tension:		400 – 2000 N (adjustable)
Tensioning speed:		250 – 340 mm/s
Power supply:	Battery	14.4VDC / 2.4 Ah NiCD
	Battery	14.4VDC / 2.7 Ah NiMH
Suspension bracket (optional)		

Advantages

- Simple one-handed operation
- Strap tensioning and welding time adjustment
- Easy strap threading; Both straps are inserted together
- Quick battery exchange



PACKAGING Datasheet P322

Battery powered manual plastic strapping tool

888-922-1622

WWW.IPACK.COM

Chart of types model P322

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.2101	P322/10/0.4-0.64	10.0	3/8"	0.40-0.64	.016-.025	2000	450	250-340	9.8-13.4
43.2102	P322/10/0.65-1.05	10.0	3/8"	0.65-1.05	.025-.041	2000	450	250-340	9.8-13.4
43.2111	P322/11.1/0.4-0.64	11.1	7/16"	0.40-0.64	.016-.025	2000	450	250-340	9.8-13.4
43.2112	P322/11.1/0.65-1.05	11.1	7/16"	0.65-1.05	.025-.041	2000	450	250-340	9.8-13.4
43.2121	P322/12/0.4-0.64	12		0.40-0.64	.016-.025	2000	450	250-340	9.8-13.4
43.2122	P322/12/0.65-1.05	12		0.65-1.05	.025-.041	2000	450	250-340	9.8-13.4
43.2123	P322/12.7/0.4-0.64	12.7	1/2"	0.40-0.64	.016-.025	2000	450	250-340	9.8-13.4
43.2124	P322/12.7/0.65-1.05	12.7	1/2"	0.65-1.05	.025-.041	2000	450	250-340	9.8-13.4
43.2131	P322/13/0.4-0.64	13		0.40-0.64	.016-.025	2000	450	250-340	9.8-13.4
43.2132	P322/13/0.65-1.05	13		0.65-1.05	.025-.041	2000	450	250-340	9.8-13.4
43.2151	P322/15/0.4-0.64	15		0.40-0.64	.016-.025	2000	450	250-340	9.8-13.4
43.2152	P322/15/0.65-1.05	15		0.65-1.05	.025-.041	2000	450	250-340	9.8-13.4
43.2153	P322/15.5/0.4-0.64	15.5		0.40-0.64	.016-.025	2000	450	250-340	9.8-13.4
43.2154	P322/15.5/0.65-1.05	15.5		0.65-1.05	.025-.041	2000	450	250-340	9.8-13.4
43.2161	P322/16/0.4-0.64	16	5/8"	0.40-0.64	.016-.025	2000	450	250-340	9.8-13.4
43.2162	P322/16/0.65-1.05	16	5/8"	0.65-1.05	.025-.041	2000	450	250-340	9.8-13.4

Battery chargers for model P322

Item No.	Model	Charging type	Tension	Countries
N5.4414	Battery standard charger	NiCd & NiMH	220-240 V / 50-60 Hz	All countries, exceptions listed below
N5.4422	Battery turbo charger	NiCd & NiMH	220-240 V / 50-60 Hz	(same as N5.4414)
N5.4416	Battery standard charger	NiCd & NiMH	240 V / 50-60 Hz	BRN, BRU, CY, EAK, EAT, GB, IRL, M, MAL, OM, SGP, Y
N5.4428	Battery turbo charger	NiCd & NiMH	240 V / 50-60 Hz	(same as N5.4416)
N5.4426	Battery turbo charger	NiCd & NiMH	110 V / 50 Hz	GB
N5.4418	Battery standard charger	NiCd & NiMH	230-240 V / 50-60 Hz	AUS, NZ
N5.4430	Battery turbo charger	NiCd & NiMH	230-240 V / 50-60 Hz	(same as N5.4418)
N5.4424	Battery turbo charger	NiCd & NiMH	110-127 V / 50-60 Hz	North and South America
N5.4420	Battery standard charger	NiCd & NiMH	220 V / 60 Hz	ROK
N5.4407	Battery mobile charger	NiCd only	-	all countries

Replacement battery for model P322

Item No.	Model	Tension	Power
N5.4309	Accu NiCd P322 / P323	14.4VDC	2.4 Ah
N5.4316	Accu NiMH P322 / P323	14.4VDC	2.7 Ah

Accessories

19.9420	Tool promotional case for P322 / P323
---------	---------------------------------------