Automatic Sidedrive 4 Tapehead Carton Sealer (AS4H)

AS4H Series

World Leader in Sophisticated Packaging Systems



AS4H Automatic Sidedrive 4 Tapehead

series overview

The new BestPack® AS4H High speed fully automatic adjustable carton sealer with Continuous Flo tape head system is for non-stop high speed sealing applications.

The new Continuous Flo tape head system features four heads. When a tape head runs low on tape, or if a tape head fails, the system will automatically switch heads so that there is continuous non-stop flow. In the mean time, the system is still sealing cartons.

The new dual sweeper kicker system reduces the chance of the sealer missing a flap even if the flaps are parallel to the conveyor.

ombine all of the above with high speed motors, and you have a dependable high speed system for the most demanding applications.

major features -

- Continuous Flo tapeheads which allow for automatic replacement when tape is low or tapehead fails
- Adjustable Bed Height from 24.5" to 30.0"
- In-line Carton Closure
- Rugged Construction
- Operator Free Design
- Cost Effective
- Width/Height Adjustment on either side of Machine
- Tape Roll Lengths: 1000 yd., 1500 yd., 2000 yd.

- Heavy Duty Frame
- UL Approved Electrical Parts
- Designed for Uniform Carton Applications
- Capable of Interchanging 2" or 3" Tape Heads
- Electrical on/off box can be mounted on either side of machine

standard features

- High Speed Motor Upgrade (Up to 125 ft./mm.)
- Dual automatic flap folder sweeper.
- Continuous Flo four head tape system.
- Interlock gates.
- PLC driven system.
- Low tape/no tape warning light.
- Unique pressure sensitive tape heads with patented tab adjustment.
- Pop out tape heads.
- Locking heavy duty casters.
- Adjustable bed height.
- Maintenance free, oil-less air system.
- Bottom tape air blowers.
- Spare parts kit.
- Instruction/parts manual.





Automatic Sidedrive 4 Tapehead Carton Sealer (AS4H)

AS4H Series

World Leader in Sophisticated Packaging Systems

optional features

- · Compatible Indexer: ARX model
- Interlock Safety Gates
- Stainless steel



Locking Castors

ARX Indexer

machine & carton specifications

• Power Requirements: 110 Volts 60 Hz

• 90 PSI, 4 - 6 CFM

• Speed: Up to 50 cartons/minute

• Tape Head: Standard: 2", Available: 3"

series comparison table

Model	Machine Dimensions	Carton Range	Cartons/Min.	Weight (lbs.)
AS4H 22-2 2" tape head	(97.6") x (39.9") x (56.5")	(7.9"-20.5) x (7.1"-14.5") x (7.9"-15.7")	Up to 50	1,034

^{*} All specifications capable of customization or subject to change without notice



888-922-1622

WWW.IPACK.COM