

World Leader in Sophisticated Packaging Systems**CS4G22** Completely Automatic Random Sidedrive w/ 4 Tapeheads**series overview**

The new BestPack® CS4G High speed fully automatic adjustable carton sealer with Continuous Flo tape head system is for non-stop high speed sealing of random applications.

All models are equipped with our exclusive Pressure Sensitive tape heads with patented Tab Adjustment Units. High Tech features such as built-in "Soft Fill" Sensors and maintenance free oil-less air cylinders set these Random Carton Sealers apart.

major features**Continuous Flo System**

The new Continuous Flo tape head system features four heads. Two tape heads on the top and two tape heads for the bottom. When a tape head runs low on tape, or if a tape head fails, the system will automatically switch heads so that there is continuous non-stop flow. There is a warning light that will tell an operator in the area that a tape head needs to be checked. In the mean time, the system is still sealing cartons.

- **Handles Random Carton Sizes**
- **Adjustable Bed Height from 24.75" to 28.0"**
- **In-line Carton Closure**
- **Reduced Cycle Time**
- **Rugged Construction**
- **Operator Free Design**
- **Cost Effective Height Sensors**
- **Tape Roll Lengths: 1000 yd., 1500 yd., 2000 yd.**
- **Heavy Duty Frame**
- **UL Approved Electrical Parts**
- **Capable of Interchanging 2" or 3" tape heads**
- **Human interface touch screen**
- **On line self diagnostic with trouble output on screen**

**PACKAGING**

888-922-1622

WWW.IPACK.COM

World Leader in Sophisticated Packaging Systems**standard features**

- Exclusive Pop-out pressure sensitive "high speed" tape head with patented tab adjustment and noise reduction arm
- Two interchangeable top head and two separate bottom high speed, continuous flo tape heads.
- Omron PLC Controls
- Indexer with Carton Centering Device
- Exclusive Automatic Flap-Fold
- Adjustable Bed Height from 24.75" to 28.0"
- Upper Side Compression
- "Soft Fill" Sensors Handles Empty/ Over Filled Cartons
- Bottom Tape Air Blowers
- "Low Tape" Warning Light
- Heavy Duty Frame and Locking Casters
- Interlock Safety Gates
- Maintenance Free, Oil-less Air Cylinders
- Operation Manual with Tools
- 125ft/min belt speed

optional features

- Stainless steel
- No tape sensor
- No flap sensor
- Retractable top or bottom tape heads
- User specified PLC brand
- Higher than 125ft/min belt speed

machine & carton specifications

- Power Requirements: 110 Volts 60 Hz
- Air Requirements: 100 PSI, 12+CFM
- Tape Head: Standard: 3"; Available: 2"

series comparison table

Model	Machine Size	Carton Range	Shipping Weight (lbs.)
CS4G 22-3 3" TapeHead	(118.5") x (31.5") x (102.6")	(9.8" - 29.5") x (6.0" - 19.7") x (5.8" - 19.7")	1,320

* All specifications capable of customization and subject to change without notice

**PACKAGING**

888-922-1622

WWW.IPACK.COM