

# Jet Printers

### VersaJet LC

### Ink Jet Printers for the Real World

Versatility and reliability is what the Little David<sup>®</sup> VersaJet<sup>®</sup> LC is all about.

Little David delivers packaging equipment that works for you



Flexible large character ink jet printer



#### The VersaJet<sup>®</sup> LC offers:

- Service Strategies
- Prints up to 6 lines
- Print on 1 or 2 production lines
- Print on 1 or 2 sides of a box
- Solution Only one controller needed
- **UL** listed
- 90 day warranty
- 2 year valve warranty

#### The VersaJet® LC replaces:

- Roller coders
- Sabor-intensive
  - marking methods
- Stencils



www.loveshaw.com

## VersaJet<sup>®</sup> LC

#### Features:

#### **Reliable Performance:**

- Over 20 years proven technology
- 2 Year warranty on valves
- 90 day warranty .

#### Flexible:

- 1 to 6 printheads
- Automatic date and time coding
- Automatic shift changes
- RS232/Rs422 serial port
- Alphanumeric incrementing
- Saves parameters with each message
- Multiple fonts available

#### **Easy Operation:**

N

- User friendly software
- Minimal operator training required
- Convenient bulk ink system



- Stainless steel for durability
- User friendly software

1 controller drives up to 6 printheads or 3 high character printheads



Standard 5-gallon bulk ink supply system includes an air pump capable of distributing ink to multiple printheads

Alleviates the need for factory supplied air line, thereby avoiding possible contaminants from this source


3/8"

1/2

VersaJet LC Print Samples:



1-1/4"



#### **Specifications:**

#### **Power Requirements:**

- 110 VAC, 60 Hz, 3 Amps maximum (switch selectable)
- Other voltages 220 VAC, 60 Hz, 1.5 Amps maximum (switch selectable)

#### **Operating Speed:**

- Up to 100' per minute (30.5m/min) (Depending on system set-up conditions)
- High speed available (Consult factory)

#### **Character Font:**

- 7 x 5 dot matrix, 7 x 10 dot matrix in bold with standard printhead
- Optional 16-dot high-character printhead

#### **Character Height:**

- 6 standard sizes: 3/8" (10mm), 1/2" (13mm), 7/8" (22mm), 1-1/4" (32mm), 1-1/2" (38mm), 2" (51mm)
- Optional high-character printhead prints at heights of 15/16" (23.8mm), 1-1/4" (32mm), and 2-7/32" (56.4mm)

#### Character Set:

 Full ASCII 64 character upper case set. Up to 39 characters per line

#### Language Options:

English, Spanish, French, Italian, German, Dutch, or Portuguese

#### **Print Direction:**

Forward, reverse or upside down

#### Memory:

15k of variable length messages

#### **Temperatures:**

- Operating 50°F to 95°F (10°C to 35°C)
- Storage 5°F to 100°F (-15°C to 38°C) •

#### **Options:**

20' printhead cable assembly available

**Distributor Information:** 



# PACKAGING

888-922-1622

WWW.IPACK.COM