

Arpac PRO-SERIES®, Arpac PRO-SERIES® Stretch Wrap Systems


PRO-SERIES® enjoys the reputation of being one of the most cost-effective semi-automatic machines on the market today. A new ergonomic sturdy design, with chains enclosed in the tower frame, ensures safer operation. Standard features include: illuminated adjustable (0-7) LED top & bottom wrap counters, top overwrap control, anti-static film rollers, cycle pause, variable speed controls for both turntable and carriage, upgraded photo eye to see most dark loads, plus EZ-LOAD Powered Pre-Stretch, maximizing stretch film usage.

The PRO-SERIES® is often purchased with the WRAP-N-WEIGH® feature that combines wrapping and weighing operations. A precision scale and digital controls are integrated into the machine which brings greater economy and efficiency to any wrapping operation requiring weighing.

This 4,000 lb. capacity system is available with a high profile turntable for forklift loading, or low profile turntable for pallet-jack loading.

The PRO-SERIES® can be customized to suit your material handling requirements with extended towers for taller loads and split frames for odd-sized larger loads.

The PRO-SERIES® is part of a robust line of stretch wrapping equipment designed to maximize stretch film usage while ensuring the very best load unitization. All ARPAC *STRETCH™* equipment is constructed with heavy-duty reinforced structural steel, and finished with non-corrosive Steel-It paint, to guarantee years of reliable wrapping. The PRO-SERIES® is manufactured in the USA and sold through our nationwide distributor network.



Features · Options · Specifications

Features

- Welded heavy-duty reinforced structural steel construction for around-the-clock operation
- Forklift portable
- 4 point caster support for HP turntable
- 6 pairs - Delrin caster support for LP turntable
- Turntable direct drive: 1/2 HP, 90 VDC motor with ANSI 50 chain
- Micro controller logic
- Top over-wrap control feature (TOC)
- Cycle pause control
- Turntable jog control
- Carriage pause control (banding)
- Adjustable dual LED wrap counters (0-7)
- Corner compensation
- Anti-static rollers
- UL approved components
- External fuses
- Positive home position alignment
- Photo electric load height sensor that detects most dark colored loads
- EZ-LOAD Powered Pre-Stretch 150-300%, 200% Standard
- Variable carriage speed (0-21 FPM)
- Turntable speed of 0-12 RPM adjustable
- Carriage drive: 1/3 HP, 90 VDC motor with ANSI chain lift drive

Options

- Extended film tower for wrapping taller loads exceeding standard machine capability
- TOP PLATEN device used to stabilize tall or light unstable loads during rotation
- A variety of access ramps to assist loading of pallet
- Split frame construction to increase film tower clearance for oversized loads
- Cycle counter to count the actual cycles of a machine operation
- Extended umbilical cords for split frame models
- More options available, consult your local ARPAC *STRETCH™* representative

Specifications

Frame	HP, LP, HP WNW, LP WNW
Turntable Options	Variety of turntable sizes are available for applications where the full skid or slip sheet needs support
Standard Turntable-HP	50" W x 50" L square
Standard Turntable-LP	60" diameter
Oversized-HP	60" W x 60" L square
Oversized-LP	72" diameter
Power Requirements-Electrical	120 V, 1 Ph, 60 Hz, 10 A
Load Sizes	A split frame design will lose up to 3" in wrap height with a standard 8' umbilical cord between the tower and the base when turntable is placed at maximum distance from the tower.
Load Height-HP	74 in
Max.Load Diagonal Clearance-HP	85 in
Load Height-LP	83 in
Max.Load Diagonal Clearance-LP	85 in
Load Height- HP WNW	72 in
Max.Load Diagonal Clearance-HP WNW	85 in
Load Height-LP WNW	81 in
Max.Load Diagonal Clearance-LP WNW	85 in
Approx.Shipping Weight-HP	1.386 lbs
Approx.Shipping Weight-LP	1.475 lbs
Approx.Shipping Weight-HP WNW	1.475 lbs
Approx.Shipping Weight-LP WNW	1.568 lbs