

Electronic Water-Activated Tape Dispenser

Better Pack® **500** Ink Jet System

Dependable Dispensing Integrates with On Demand Printing



The Better Pack 500 IJ system offers rugged and reliable performance of an easy-to-operate tape dispenser with the added power of an integrated ink jet printer. The Better Pack Ink Jet gives you the ability to print directly on the tape as it is dispensed and the option to change the printed message as needed without changing ink pads. And, it can hold up to three logos at a time.

The Better Pack 500 IJ is engineered for durability, ease of use and safety! It is fast and reliable and will improve the efficiency and speed of operations with medium to high volume packaging needs.

Ink Jet Kit

- High resolution ink jet printer, 300 dpi
- Ink cartridge system...no more ink spills
- Ability to purchase entire system or components!
- Ink jet powered by Hewlett Packard
- Print head in Ink Cartridge

Ink Jet Software

- Variable character heights
- Print up to 3 logos in either one line mode or the two line mode
- Time and date stamping
- Stores up to 99 messages

Complete Standard System includes:

A controller with 4 line x 16 character LCD and tactile keypad for message entry. A high resolution print head module with complete mounting bracket.

Electronic Water-Activated Tape Dispenser

Better Pack® **500** Ink Jet System

Standard Operating Features

Controller:

- Alpha/Numeric character set plus special characters
- Character heights: 1/2" (12.7mm) and 7/32" (5.5mm)
- Message length: 24 Characters of 1/2" height 48 Characters of 7/32" height (24 per line)
- Print resolution: 300 dpi at 200 feet per minute (61m)
- Programmable line speed
- Programmable print delay
- Programmable print direction
- Multiple language prompts: English and Spanish
- Inverted Printing
- Inter-character spacing

Ink Supply:

- Cartridge volume; 42cc
- Colors: Black, Blue, Red, Green, Yellow
- Low ink monitoring

Power Required: 110-240 VAC, 50-60Hz 0.5a

Environmental: 50F - 104F (10C - 40 C)

Up to 80% RH non-condensing

Physical Dimensions: Controller: 8.75" L x 4.125" W x 1.5" D

Print head Module: 4" L x 2" W x 3" H



Dispenser Specifications

Dimensions: 18.0" L x 12.0" W x 10.5" H

Shipping weight: 30 lbs.

Tape roll capacity:

- 1.5" to 3" wide
- Up to 7.5" diameter
- Up to 600' length roll

Dispensing speed: 45" per second

Dispensing length:

- 6" to 45" using one of 14 preset length keys
- Up to 90" using 2X key
- Up to 120" using Random key

Blades: Guillotine shear with easy blade lifter

Water brushes: 3

Water bottle capacity: 44 ounces (1.3 liters)

Electrical requirements: Available in 115 volt and 230 volt models

Safety compliance: Meets or exceeds UL, CE and CSA standards

Warranty: 2 years parts and materials, 6 months labor

