

LITTLE DAVID 



LS-800DT

AUTOMATIC PRINT/APPLY APPLICATOR

The Little David® LS-800DT has all the same features as the LS-800 except that it gives you the ability to print and apply labels on almost any panel or combination of two adjacent panels, including corner wrap.

FEATURES:

- Print and applies a corner wrap, dual tamp, front-side-back only label and ability to apply label to bottom edge of product


SPECIFICATIONS:

Machine Dimensions:

- Length: 46 3/8"
- Width: 18 3/4"
- Height: 24 3/16"
- Weight: 100 lbs.

Label Dimensions:

- Width: 1" - 5-1/4" Length: 1/2" - 14"
- Roll Outside Diameter: 11-7/8", 15-7/8" optional
- Core Diameter: 3", 4" optional for labels over 6" long
- Label Conversion Specifications: Pressure sensitive die cut with 1/8" gap. Labels with no gap and/or clear labels require an "eye mark"
- Power Requirements: 115 - 230 volts; 50/60 cycle; 5 Amps (requires two outlets)
- Air Requirements: 40 - 60 PSI at .5 CFM while dispensing
- Dispense Rate: Up to 16"/second based on printer selection



FEATURES/DATA FOR ALL LABELERS:


- Microprocessor controller with user-friendly keypad and LCD display for easy access to label application parameters.
- Simple threading path ensures quick label change
- Balanced feed assures consistent label tension and reduces web breakage
- Non-cantilevered dual frame design that eliminates web drift
- Accuracy: +/- 1.32" (+/- .79mm) when product delivery is consistent
- Product Sensing: Photoelectric (diffused - proximity)
- Over 50 save areas for quick recall of label placement settings
- Label Sensing: Photoelectric

AVAILABLE OPTIONS:

- Customized conveyor system
- Various mounting
- Label generation software available
- Various product sensors
- Printer selection (Sato, Zebra, Datamax, Avery DPM) for Print/Apply Applicators
- Parallel (IEEE1284), Ethernet-10/100BaseT, wireless communication (Sato only) interfaces for Print/Apply Applicator
- 305 dpi print resolution for Print/Apply Applicators
- Low media, web breakout and media out signal alarm beacon
- Direct thermal for Print/Apply Applicators
- Various applicator heads
- Left or right hand dispensing option
- 3 condition light tower, audible alarm
- PLC integratable for system solutions
- Touch and Go Smart

LABELERS

HIGH PERFORMANCE SOLUTIONS
FOR THE REAL WORLD



LITTLE DAVID® DELIVERS HIGH-PERFORMANCE PACKAGING EQUIPMENT.